(i) Coming October 20th, discover our sleek new design and powerful features. <u>Learn More</u>

UL Product iQ®



Extinguishing System Attachments

COMPANY

SHIELD FIRE SAFETY & SECURITY LTD

Unit 3, Endeavour Dr Basildon, SS14 3WF United Kingdom

S9078

Supervisory switches, SD-SVS-OSYJM

SPRINKLER SYSTEM ALARM INITIATING DEVICES

Wet pipe, paddle type

Model	Size In.	Pipe Schedule	Max System Pressure psig
SD-WFD10T	1.00	10 thru 40	175
SD-WFD12T	1.25	10 thru 40	175
SD-WFD15T	1.50	10 thru 40	175
SD-WFD20T	2.00	10 thru 40	175
SD-WFD20	2	10 thru 40	175
SD-WFD25	2.5	10 thru 40	450
SD-WFD30	3	10 thru 40	450
SD-WFD40	4	10 thru 40	450
SD-WFD50	5	10 thru 40	450
SD-WFD60	6	10 thru 40	450
SD-WFD80	8	10 thru 40	450
SD-WFD100	10	10 thru 40	300

SD-WFD-JM	2.00	10 through 40	365
	2.5	10 through 40	365
	3.0	10 through 40	365
	4.0	10 through 40	365
	5.0	10 through 40	365
	6.0	10 through 40	365
	8.0	10 through 40	365

SUPERVISORY SIGNAL INITIATING DEVICES

Supervisory switches

Model	Oper Pressure psig	Max System Pressure psig	
SD-SVS OSY-1	N/A	N/A	
SD-SVS OSY-2	N/A	N/A	
SD-SVS OSY-3	N/A	N/A	
SD-SVS IP-1	N/A	N/A	
SD-SVS IP-2	N/A	N/A	
SD-SVS IP-3	N/A	N/A	

SPRINKLER SYSTEM ALARM INITIATING DEVICES

Wet pipe, paddle type

Model	Size In.	Pipe Schedule	Max System Pressure psig
SD-WFD10TW	1	10 thru 40	450
SD-WFD12TW	1.25	10 thru 40	450
SD-WFD15TW	1.5	10 thru 40	450
SD-WFD20TW	2	10 thru 40	450
SD-WFD20W	2	10 thru 40	450
SD-WFD25W	2.5	10 thru 40	450
SD-WFD30W	3	10 thru 40	450
SD-WFD40W	4	10 thru 40	450
SD-WFD50W	5	10 thru 40	450
SD-WFD60W	6	10 thru 40	450
SD-WFD80W	8	10 thru 40	225







Last Updated on 2025-10-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."