

Model SD-YS300FF-D

File Number: EX16175

COMPANY

SHIELD FIRE SAFETY & SECURITY LTD

Unit 3, Endeavour Dr
Basildon, SS14 3WF United Kingdom

MODEL INFO

SD-YS300FF-D

Y-Type

PRODUCT DETAILS			
End-configuration	Size, NPS	Rated Pressure, psi (kPa)	Approximate Loss of Head at 15 ft/sec (4.6 m/sec) flow velocity
ASME/ANSI B 16.1 Flange	2 in.	300 (2068)	6.7 psi (47 kPa)
ASME/ANSI B 16.1 Flange	2.5 in.	300 (2068)	4.2 psi (29 kPa)
ASME/ANSI B 16.1 Flange	3 in.	300 (2068)	3.8 psi (27 kPa)
ASME/ANSI B 16.1 Flange	4 in.	300 (2068)	3.8 psi (27 kPa)
ASME/ANSI B 16.1 Flange	5 in.	300 (2068)	4.3 psi (30 kPa)
ASME/ANSI B 16.1 Flange	6 in.	300 (2068)	4.4 psi (31 kPa)
ASME/ANSI B 16.1 Flange	8 in.	300 (2068)	3.9 psi (27 kPa)
ASME/ANSI B 16.1 Flange	10 in.	300 (2068)	3.6 psi (25 kPa)
ASME/ANSI B 16.1 Flange	12 in.	300 (2068)	3 psi (21 kPa)

Feedback



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."